

SUTTNER ST-810 Front Entry

Front inlet design keeps dirty hose away from operator.

- 8 GPM maximum
- 3050 PSI maximum
- 320°F. maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part
1479



ST-1100 Lightweight

Perfect for cold water units in factories or smaller hot water units

- 7 GPM
- 3050 PSI
- 300°F. max
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
4126	ST-1100



ST-1500H Open Gun

Specialty use gun

Ideal when unloader is unavailable or for manual start pressure washer.

- 12 GPM maximum
- 4000 PSI maximum
- 300°F. maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
1291	ST1500H



MTM407

- 7 GPM maximum
- 4000 PSI maximum
- 250°F. maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part
6150



MV2005

- 8 GPM maximum
- 4000 PSI maximum
- 300°F. maximum
- 3/8FPT inlet
- 1/4FPT outlet

Part	Model
6110	MV2005
6109	Kit



Karcher Style Spray Gun

- 7 GPM max
- 4000 PSI max
- 300°F. maximum
- 22mm male in/out

Part
6069



YRL51 Gun

- 13.2 GPM maximum
- 4050 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part
6267



5030 Gun

- 12 GPM maximum
- 4500 PSI maximum
- 300°F. maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
1740	5030
1733	Kit



AL35

Easy pull trigger even at 5000 PSI!

- 8 GPM maximum
- 5000 PSI maximum
- 300°F. maximum
- 3/8" brass inlet
- 1/4" discharge

Part	Model
6522	AL35
6524	Kit



Spray Guns

Excellent choice for heavy industrial applications.

- 10 GPM maximum
- 5000 PSI maximum
- 300°F. maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model	Outlet
1480	21250B	SS
2341	21290C	Brass
1632	Repair kit	



VEGA/YG4000 Gun

Ergonomic designed hand guard
Easy trigger pull

- 10 GPM maximum
- 5000 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
3452	VEGA
3453	Kit



ST-1500 Top Seller

Streamline designed to be “universally” comfortable, even for very small hands.



- 10.4 GPM max
- 5000 PSI max
- 300°F max
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
1475	ST-1500
1528	Kit 4000 PSI
5106	Kit 5000 PSI

ST-1500W Weep Gun

Weep allows water to continue flowing after trigger is released. Prevents gun freeze



- 10.4 GPM maximum
- 5000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
2324	ST-1500W
1528	Kit 4000 PSI
5106	Kit 5000 PSI

ST-2000 Big Hand Gun



Ideal for rental machines

Designed for heavy duty durability.
Takes the heat and abuse.

Easy access to replace cartridge valve.

- 10.4 GPM max
- 5000 PSI max
- 300°F max
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
1477	ST-2000
1528	Kit 4000 PSI
5106	Kit 5000 PSI

ST-2305 Easy Pull!!



The SUTTNER exclusive trigger, reduces trigger opening force by up to 50% compared to all other rear entry spray guns.

- 12 GPM maximum
- 5000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
4654	ST-2305
4540	Repair kit
6792	Ceramic ball kit

ST-2605 Relax Action



True over center cam

Easiest opening and holding trigger.

SUTTNER exclusive trigger ideal for working long hours. Reduces trigger force up to 20% holding force up to 60%

- 12 GPM maximum
- 5000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
4539	ST-2605
4540	Repair kit
6792	Ceramic ball kit



RL30/YG5000 Gun

Trigger design for easier pull at higher pressures

Larger, more comfortable hand grip space to accommodate gloves



- 10 GPM maximum
- 5000 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
4855	RL30/YG5000
6228	Repair kit

DG5010 Spray Gun



- 10 GPM maximum
- 5000 PSI maximum
- 300°F. maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part
6906

KEW Style Spray Gun



With bayonet coupler and plug on outlet

- 10 GPM maximum
- 5000 PSI maximum
- 300°F maximum

Part	Model
6907	KEW w/coupler & plug
6123	Coupler replacement
6140	Plug replacement

Chemical Resistant Guns

SUTTNER ST-810 POM

Front entry gun is the best chemical application gun with a stainless steel spring, needle, ball and a poly seat for chemical resistance

- 8 GPM maximum
- 2000 PSI maximum
- 320°F. maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part
6561

ST-2315 w/Ceramic Ball

Ceramic ball in valve is highly resistant against nearly all soaps and acids.

Suttner exclusive "relax-action trigger and comfort grip reduces trigger force up to 40% and holding force up to 90%
Unitized valve for easy repair

- 12 GPM maximum
- 5000 PSI maximum
- 300°F. maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Model
6916	ST2315 Gun
6792	Ceramic Ball Kit



YG5000C Gun

With ceramic ball for use with chlorine & acid

- Ceramic ball for excellent corrosion resistance
- Forged brass body with stainless wetted parts
- Trigger lock to prevent accidental activation
- Comfortable impact resistant housing

- 10.5 GPM maximum
- 5000 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet



Part	Model
6418	YG5000C
6425	Repair kit

Stainless Steel Guns

SUTTNER ST-3300

Replaces ST-3002.

Highest **volume** rated industrial gun.

- Forged stainless steel housing, piston, and malleable seat.
- Special heat and chemical resistant seals

- 27 GPM maximum
- 2170 PSI maximum
- 300°F. maximum
- 1/2" FPT inlet
- 1/2" FPT outlet



Part
6708

SUTTNER ST-2700

- Stainless steel internal components.
- Suitable for corrosive chemical usage
- "Relax action" trigger and comfort grip reduces trigger force up to 20%
- Unitized valve for easy repair

- 12 GPM maximum
- 5000 PSI maximum
- 300°F maximum



Part	Model
4730	ST2700SS
5609	Standard Repair kit
6792	Ceramic Ball Kit

ST-3600 Gun

Suttner's highest **pressure** rated industrial gun.

- Forged stainless steel housing, piston, and malleable seat.
- Special heat and chemical resistant seals

- 21 GPM maximum
- 8700 PSI maximum
- 300°F maximum
- 1/2" FPT inlet
- 1/2" FPT outlet



ST-3600 Lance

- Perfect fit for the ST-3600 gun.
- Stainless steel construction is ideal for chemical applications
- Adjustable handle

- 1/2" FPT inlet
- 1/4" FPT outlet



Part	Product
6714	Gun
6732	39" Lance

Linear/Straight Guns

SUTTNER ST-601

Heavy duty impact trigger guard has made ST-601 an industry standard for telescopic wand manufacturers. Ideal for cleaning vertical & overhead surfaces.

- 12 GPM maximum
- 4000 PSI maximum
- 300°F. maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
2396	ST-601
1528	Repair kit



YG4000S

Straight spray gun. Insulated handle remains cool at maximum fluid temperature

- 10.5 GPM maximum
- 3650 PSI maximum
- 320°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
3451	YG4000S
3450	Repair kit



High Volume, Low Pressure Guns

SUTTNER ST2620

For high volume, low pressure machines!



Hold trigger open with one finger
Relax action trigger reduces hand fatigue
Easiest opening & holding trigger in class
Proper spray angle for optimum position

- 21 GPM maximum
- 1800 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Part
6936	ST2620
4540	Repair Kit

ST2720 Stainless Steel



Ideal for high volume, low pressure applications such as farms, chemical or food processing industries!
Stainless steel valve components create a durable, long lasting gun

- 21 GPM maximum
- 1800 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Part
6937	ST2720
5609	Repair Kit

YG1732 Heavy Duty Gun



- Shockproof plastic housing
- Construction of stainless steel & brass
- Ergonomic construction
- Trigger operation minimizes fatigue
- 32 GPM maximum
- 1740 PSI maximum
- 210°F maximum
- 1/2" FPT inlet
- 1/2" FPT outlet

Part
3481

Specialty Gun/Lance Combos

M407 w/Molded Grip Lance



Quick connect plug on inlet
Lance extension w/ quick connect socket on outlet

- 8 GPM maximum
- 4000 PSI maximum
- 300°F maximum
- 3/8" FPT inlet
- 1/4" FPT outlet

Part	Model
6843	With 24" mg lance
6273	With 36" mg lance
5889	With 48" mg lance

DG3200M Rear Entry w/Extension



- One piece
- 6.5 GPM max
- 3200 PSI max
- 22mm outlet
- 195°F max

Part	Model
6788	3/8" FPT Inlet
6737	22mm Male Inlet

Hobby Hose, Gun, Lance Kits

- 1/4"x22mmx22mm hose
- 1piece gun 22mm I/O w/12" extension
- Additional 18" wand pipe extension
- 6.6 GPM maximum
- 3000 PSI maximum



Part	Product
6132	Kit w/QC outlet
5418	Kit w/3.5 hi-lo nozzle
6081	Lance w/3.5 hi-lo nozzle

Plastic Low Pressure Guns

To be used for chemical pre spray, or to spray acids.



- 2 GPM maximum
- 150 PSI maximum
- 100°F maximum

Part	Model
4494	Spraying system 1/4" FPT inlet 15"
1633	Spraying Systems 3/8" hose barb inlet
2201	Cone jet angled assembly (4494, 1633)

RLW40 Dump Gun



Excellent for car washes.

- 10.5 GPM maximum
- 3050 PSI maximum
- 140°F maximum
- 3/8FPT inlet
- 1/8FPT outlet

NOTE: Trigger will not pull unless under pressure

Part	Model
1046	16"
2375	40"
2376	Repair kit

ST1500 w/Bendable-Wand



ST-10 nozzle protector

Part
6826